

# The New TK-2000/3000

## Slim, Thin and Light

### With All-in-one Package



#### Supplied Accessories



#### All-in-one Package

The TK-2000/3000 is ready for use immediately after purchase. It comes with all necessary original accessories, including a charger, Li-Ion battery pack and antenna. A handy belt clip is also provided. There is no need to buy extra accessories for normal operation.



#### Thin & Lightweight

Thinner and lighter – the TK-2000/3000 is ideal for hooking on a belt or even slipping into a coat pocket. The slim design fits neatly in your hand and it weighs only 203g with the Li-Ion battery.



#### Robust & Reliable

The TK-2000/3000 is built to survive hard knocks, drops and all-weather environments. It meets or exceeds the stringent IP54 dust and water intrusion standards as well as the MIL-STD 810 C, D, E, F & G environmental standards.



#### 16 Channels with Scan Function

This compact, user-friendly portable offers a total of 16 channels, and each can be assigned a QT and DQT tone key to eliminate unwanted signals. You can also assign the 16th channel, if free, to the scan function. This added convenience means that the PF key is freed up for some other function.



#### Programmable Function Key with Hold

The side PF key can be programmed for enhanced operating ease, while the adjustable Hold feature doubles the number of functions at your fingertips.



#### Other Features

- Output Power 5W (VHF) / 4W (UHF)
- QT / DQT • DTMF Enc. (PTT ID, Autodial)
- Priority Scan
- Windows® Programming and Tuning
- Wide/Narrow Channel Bandwidth
- VOX ready • Battery-Saver
- Busy Channel Lockout
- Time-Out-Timer
- Low-Battery Alert • Tri-Colour LED
- Wired Clone
- Wide selection of operating frequencies (440 - 480Mhz)



www.kenwood.com

## The Thin Edge

Kenwood's TK-2000/3000 is supremely easy to handle and to operate. Yet this handy compact radio is extremely reliable, meeting the famously tough MIL-STD 810 C/D/E/F and G specifications. With its well-balanced performance, it makes perfect business sense – especially for inventory control and service industry operations.



## Accessories Options

■ **KNB-63L**  
Li-Ion Battery  
(7.2V, 1,100 mAh)



■ **KSC-35S**  
Rapid Charger



■ **KRA-22**  
VHF Low Profile  
Helical Antenna



■ **KRA-23**  
UHF Low Profile  
Helical Antenna



■ **KRA-26**  
VHF Helical Antenna



■ **KRA-27**  
UHF Whip Antenna



■ **KHS-26**  
Clip Microphone  
with Earphone



■ **KMC-21**  
Compact Speaker  
Microphone



■ **KHS-1**  
Headset  
with VOX/PTT



■ **KHS-21**  
Headset



■ **KWR-1**  
Water Resistant Bag



All accessories and options may not be available in all markets.  
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

## Specifications

	TK-2000	TK-3000
<b>GENERAL</b>		
Frequency Range		
Type 1	144 - 174 MHz	440 - 480 MHz
Type 2	—	400 - 430 MHz
Number of Channels	16 channels	
Channel Spacing		
Wide / Narrow	25 kHz / 12.5 kHz	
Channel Step	5, 6.25 kHz	
Operating Voltage	7.5 V DC $\pm 20\%$	
Battery Life (5-5-90 duty cycle, save off)		
with KNB-63L	Approx. 10 hours	
Operating Temperature	-20°C ~ +60°C	
Frequency Stability	5 ppm	2.5 ppm
Antenna Impedance	50 $\Omega$	
Channel Frequency Spread	30 MHz	40 MHz
Dimensions (W x H x D), Projections not Included		
Radio only	54 x 113 x 14 mm	
with KNB-63L	54 x 113 x 24.9 mm	
Weight (net)		
Body only	Approx. 130 g	
with KNB-63L	Approx. 203 g	
FCC ID		
Type 1	ALH437200	ALH437300
Type 2	—	ALH437301
FCC Compliance	Parts 15 / 90	Parts 15 / 90

	TK-2000	TK-3000
<b>RECEIVER</b>		
Sensitivity (12 dB SINAD)		
Wide / Narrow		0.25 $\mu$ V / 0.28 $\mu$ V
Selectivity		
Wide / Narrow		70 dB / 60 dB
Intermodulation Distortion		
Wide / Narrow		65 dB / 60 dB
Spurious Response	65 dB	60 dB
Audio Distortion		Less than 5 %
Audio Output		500 mW / 8 $\Omega$
<b>TRANSMITTER</b>		
RF Power Output (High / Low)	5 W / 1 W	4 W / 1 W
Spurious Response		65 dB
Modulation		
Wide / Narrow		16K0F3E / 11K0F3E
FM Hum & Noise		
Wide / Narrow		45 dB / 40 dB
Audio Distortion		Less than 5 %

Measurements made per TIA/EIA 603 and specifications shown are typical. Kenwood follows a policy of continuous advancement in development.

For this reason specifications may be changed without notice.

Windows® is a registered trademark of Microsoft Corporation.

Measurements made per TIA/EIA 603 and specifications shown are typical.  
Kenwood follows a policy of continuous advancement in development.  
For this reason specifications may be changed without notice.

Windows® is a registered trademark of Microsoft Corporation.

## Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure II	506.2/Procedure II	506.3/Procedure II	506.4/Procedure III	506.5/Procedure III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV

### International Protection Standard

Dust & Water Protection IP54

To meet MIL810 and IP54, the 2-pin connector cover has to be connected.

## Listen to the Future

Kenwood has always connected with people through sound. Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment.

## Kenwood Corporation

### Communications Equipment Division

1-16-2 Hakusan, Midori-ku, Yokohama-shi, Kanagawa, 226-8525 Japan

www.kenwood.com



ISO9001 Registered  
Communications Equipment Division  
Kenwood Corporation